





# Vivace Decorative (Glazed Porcelain)



Rice - RIC  
NATVIVRIC44G  
4"x4" Pressed Porcelain Field Tile - Gloss



Rice - RIC  
NATVIVRIC49G  
4"x9" Pressed Porcelain Field Tile - Gloss



Rice - RIC  
NATVIVRIC918M  
9"x18" Pressed Porcelain Field Tile - Matte



Fossil - FOS  
NATVIVFOS44G  
4"x4" Pressed Porcelain Field Tile - Gloss



Fossil - FOS  
NATVIVFOS49G  
4"x9" Pressed Porcelain Field Tile - Gloss



Fossil - FOS  
NATVIVFOS918M  
9"x18" Pressed Porcelain Field Tile - Matte



Atlantic - ATL  
NATVIVATL44G  
4"x4" Pressed Porcelain Field Tile - Gloss



Atlantic - ATL  
NATVIVATL49G  
4"x9" Pressed Porcelain Field Tile - Gloss



Atlantic - ATL  
NATVIVATL918M  
9"x18" Pressed Porcelain Field Tile - Matte



**Caviar - CAV**  
NATVIVCAV44G  
4"x4" Pressed Porcelain Field Tile - Gloss



**Caviar - CAV**  
NATVIVCAV49G  
4"x9" Pressed Porcelain Field Tile - Gloss



**Caviar - CAV**  
NATVIVCAV918M  
9"x18" Pressed Porcelain Field Tile - Matte



**Motif Rice**  
NATVIVMOTRIC44G  
4"x4" Pressed Porcelain Deco - Gloss



**Incline Rice**  
NATVIVINCRIC44M  
4"x4" Pressed Porcelain Deco - Matte



**Roads Atlantic**  
NATVIVROAATL99M  
9"x9" Pressed Porcelain Deco - Matte



**Peak Caviar**  
NATVIVPEACAV99G  
9"x9" Pressed Porcelain Deco - Gloss




**Roads Caviar**  
NATVIVROACAV99M  
9"x9" Pressed Porcelain Deco - Matte

**SIZING & PACKAGING**

| Type  | Shape | Item Code       | Size     | Description                                     | Pcs / Ctn | Sf / Ctn |
|-------|-------|-----------------|----------|---|-----------|----------|
| Field |       | NATVIV---44G    | 4"x4"    | Pressed Porcelain Field Tile - Gloss            | 40        | 5.38     |
|       |       | NATVIV---49G    | 4"x9"    | Pressed Porcelain Field Tile - Gloss            | 20        | 5.38     |
|       |       | NATVIV---918M   | 9"x18"   | Pressed Porcelain Field Tile - Matte            | 10        | 10.87    |
| Deco  |       | NATVIVMOTRIC44G | 4"x4"    | Pressed Porcelain Deco - Gloss (Motif Rice)     | 40        | 5.38     |
|       |       | NATVIVINCRIC44M | 4"x4"    | Pressed Porcelain Deco - Matte (Incline Rice)   | 40        | 5.38     |
|       |       | NATVIVPEACAV99G | 9"x9"    | Pressed Porcelain Deco - Gloss (Peak Caviar)    | 20        | 10.80    |
|       |       | NATVIVROACAV99M | 9"x9"    | Pressed Porcelain Deco - Matte (Roads Caviar)   | 20        | 10.80    |
|       |       | NATVIVROAATL99M | 9"x9"    | Pressed Porcelain Deco - Matte (Roads Atlantic) | 20        | 10.80    |
| Trim  |       | ∅ NATVIV---LNRG | 1/2"x12" | Pencil Liner - Gloss                            | 50        | -        |

**ANSI TECHNICAL SPECIFICATIONS - Gloss**

|         | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|--------------|------------------------|-----------------------------|-------------------------|------------------------------|-----------------------------|--------------------------------|
| Results | N/A          | 3                      | Unaffected                  | 6                       | ISO ≥ 600 N                  | ≤ 0.5%                      | Unaffected                     |



**ANSI TECHNICAL SPECIFICATIONS - Matte**

|         | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|--------------|------------------------|-----------------------------|-------------------------|------------------------------|-----------------------------|--------------------------------|
| Results | ≥ 0.42       | 4                      | Unaffected                  | 7                       | ISO ≥ 600 N                  | ≤ 0.5%                      | Unaffected                     |



**APPLICATIONS - Gloss**

|             | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|-------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | ●      | ◻     | ◻           |               | ◻            | ◻          |
| Commercial  |        | ◻     | ◻           |               | ◻            | ◻          |



**APPLICATIONS - Matte**

|             | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|-------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | ●†     | ◻     | ◻           | ◻             | ●†           | ◻          |
| Commercial  | ●†     | ◻     | ◻           | ◻             | ●†           | ◻          |



**LEGEND**

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- \* Special Order only



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

The maximum allowable installation offset is 33%. Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook. Use of a leveling system is strongly recommended.

For installation of all gloss, polished, polished glazed, lappato, and honed porcelain/ceramic tiles, use a grout release prior to grouting to prevent absorption of the grout into the tile's micropores. Use a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the polished or honed tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. We reserve the right to make product changes at any time without notice.