



# **GLASS MOSAICS**



SPARKLING SAND JT01



SEA GLASS SHIMMER JT04




BONFIRE JT07



BEACH PEBBLE JT02




AMBER WAVE JT05



SUNSET PATH JT08



SILVER SHORE JT03



COBBLESTONE JT06





#### SIZES

		Thickness	Sq. Ft./ Carton	Pieces/ Carton
5/8" Random Mosaic (Mesh-mounted on a 12 x 12 sheet)	(12-5/16" x 12-3/16" Sheet) (31.30 cm x 30.90 cm Sheet)	5/16"	11.22	11

## **APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	<b>✓</b>
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest ", visit daltile.com/DCOF.

## APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

#### INSTALLATION

Grout Joint Recommendation	Shade Variation	
1/8" Approximately	Random (V4)	

### PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

### NOTES

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

